



CONTENTS:

Page 1	Specifications
Page 2	Safety Information
Page 2	Operating Instructions
Page 2	Preventative Maintenance and Calibration
Page 2	Warranty Information



SPECIFICATIONS	
Color	Torque Setting
Yellow	65 ft/lbs
Blue	80 ft/lbs
Gray	100 ft/lbs
White	120 ft/lbs
Lt Blue	140 ft/lbs



SAFETY INFORMATION

For your safety, read, understand, and follow the information provided before first use. It is essential to have qualified personnel involved in the use and operation of torque tools that have been trained and qualified in its safe operation and proper use.

It is the responsibility of the owner and operator to study and understand this product and follow the safety instructions prior to using the tool. If the operator is not fluent in English, the product and safety instructions shall be read and discussed in the operator's native language by the purchaser, owner, or his designee. A copy of these instructions should be kept intact and located in a convenient location for future reference.

OPERATING INSTRUCTIONS

Preset torque wrenches do not need adjustment prior to use. Select the torque wrench with the proper torque rating for the application. After tightening the fastener by hand apply force to the handle of the torque wrench until you hear an audible "click." This designates specified torque value have been achieved. **DO NOT CONTINUE TO TIGHTEN OR REPEAT AS IT WILL RESULT IN OVERTIGHTENING BEYOND SPECIFIED TORQUE LIMITS.**

PREVENTATIVE MAINTENANCE AND CALIBRATION

Torque Wrenches are fine precision instruments and should not be mistaken for a ratchet or other hand tool. In order to maintain accuracy and long service life they should never be oiled, dropped, thrown, submerged in fluid, or used in a manner they weren't designed for.

For best results clean torque wrench after each use to remove any excess dirt, grease, or oil. Place torque wrench back in blow mold case or other protective area to prevent accidental damage. Calibration of the torque wrench should be checked every 5,000 clicks/cycles or once annually. Email sales@affjaxx.com to get information on the nearest torque wrench repair center.

WARRANTY INFORMATION

American Forge & Foundry warrants to the original purchaser of torque wrenches that the products are free from defects in workmanship and materials. American Forge & Foundry will repair or replace torque wrenches which fail to give satisfactory service due to defective workmanship or materials (excluding calibration) for a period of 1 year from date of original purchase. American Forge & Foundry warrants "out of box" calibration of each new and unused torque product. Repair, replacement, or recalibration shall be at the election and expense of American Forge & Foundry, and is your exclusive remedy in place of all other rights and remedies. Products must be returned with proof of purchase to a designated repair center.

American Forge & Foundry does not provide warranty for products subjected to abnormal use. Abnormal use includes misuse, accident, modification, unreasonable use, neglect, lack of maintenance, or use after the tool is significantly worn.